

## Maintenance and protection for all lacquered parquet and wooden floors

### Characteristics

Floorservice Parquet Polish protects wooden floorings, renews the satin glow of the lacquered surface and makes the flooring water- and dirt repellant.

### Applications

Periodical maintenance and protection of all lacquered parquet and wooden floor surfaces.

### Contains

Floorservice Parquet Polish is based on poly-acrylate dispersions.

### Technical data

**Working temperature:** 10 – 25° C

**Drying time:** about 60 minutes

**Usage:** 1 liter = approx. 60 – 80 m<sup>2</sup>

**Storage:** away from frost

**Packing:** 1000 ml

### Instructions for use

Shake well.

Lacquer must be at least 3 weeks old before applying Floorservice Parquet Polish. Do not use on waxed or oiled floors.

Apply undiluted product evenly over a clean and dry floor using a cloth (free of fluff), e.g. 3 to 4 times a year. Apply Parquet Polish always in the direction of the wood grain and do not rub in the opposite direction to avoid stripes. To clean your floor (e.g. weekly) use Floorservice Parquet Cleaner. To clean your floor thoroughly and to remove build-up Polish-layers, use Floorservice Polish Remover.

**Important:** Especially parquet or laminated floors are not to be wet during a longer period of time. Always pay attention to the instructions of the producer of the floor.

*Above product information and recommendations are given in good faith and based on practical tests following long term research and development. We cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. In cases of doubt always test the product in advance.*

29.10.2013

